



NOTES:

1. ALL 9 GAUGE FABRIC WIRE SHALL HAVE 59C.C. OF ZINC/.09m UNDER BLACK VINYL COATING
2. ALL CONCRETE SHALL BE 20 MPa.
3. ALL FRAME WORK AND OTHER FENCE COMPONENTS SHALL BE FINISHED WITH BLACK GLOSS ENAMEL BY POWDER COAT APPLICATION.
4. ALL FASTENERS ARE TO BE BLACK VINYL COATED
5. CORNER POSTS SHALL BE INSTALLED AT HORIZONTAL DEFLECTIONS IN THE FENCE LINE OF 10 DEGREES OR MORE.
6. TERMINAL POSTS SHALL BE INSTALLED AT EQUAL INTERVALS NOT EXCEEDING 150m. ADDITIONAL TERMINAL POSTS SHALL BE INSTALLED WHERE CHANGES IN VERTICAL ALIGNMENT OF FENCE EXCEED 30 DEGREES
7. FOR FOOTING DETAILS REFER TO OPSD-972.130
8. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN.

1.2M HIGH BLACK COATED VINYL FENCE



DWG DATE:
FEB 20, 2013

REVISION DATE:

DWG NO:
900